


Product Information Hose Pump SP-550-2



Application areas:

- Special foundation engineering, Tunnelling (bored pile, cut-off wall, jet grouting)
- Biogas production



Pumping of:

- Bentonite slurries, drilling fluids, sealing wall slurries, groundwater, mortar, slurries, dirty water; cement, fly ash or other solid-containing slurries
- Return suspensions
- Slurries
- Biomasses, Press water

Flow rate speed n1	max. 6	m³/h
Flow rate speed n2	max. 12	m³/h
Discharge pressure	max. 6	bar
Suction lift	max. 8	m
Solids grain size	max. 16	mm
Medium temperature	50	°C
Nominal diameter of hose	50	mm
Suction connection	Storz C	2" standard coupling DIN 14307, alternatively 2" AG, flange DN50 PN16
Pressure connection	Storz C	2" standard coupling DIN 14307, alternatively 2" AG, flange DN50 PN16
Power connection	CEE-plug	16 A, 5-pole
Power input	4,5	kW
Voltage	400	V; 50 Hz
Dimensions	0,63 x 0,69 x 1,12	m (L x W x H)
Weight	approx.174	kg

)* The stated values are approximate values and refer to the pumping of water with 18 ° C. Conditionally by abrasion of the hose pump, unfavourable suction, pressure conditions and influence of viscosity of the pumping medium may differ the actual performance data from the specified data.

Technical Data / Performance Data *

GERTEC

Maschinen- und Anlagenbau GmbH

> Gewerbepark 3 D-87477 Sulzberg

Phone: +49(0)8376-987 91-0 Fax: +49(0)8376-987 91-99 info@gertec-gmbh.de

Art.No.: 37388 Edition: 2022-02-09 Technical specifications are subject to change page 1 / 2



Product Information Hose Pump SP-550-2

Features:

- Pump housing with housing cover in standard steel version
- ✓ Moveable pump frame (rubber tires)
- Pump drive with rotor bearing and flange bearing in the housing cover 2 flow rates by 2 different conveying speeds
- ✓ **Pump rotor** with rotatable mounted pressure rollers
- ✓ Steel pressure roles with roller bearings and eccentric adjustment (wear compensation of hose pump)
- Electrical function and power control with the following display and control elements:
 - Main switch ON/OFF
 - Pump ON/OFF
 - Selector switch reversing operation (forward/backwards)

Accessories (not included in delivery):

- \circ Suction filters / suction tubes
- o Suction and discharge hoses
- o Suction and pressure connections in Storz or Perrot
- o Frequency converter

GERTEC

Maschinen- und Anlagenbau GmbH

> Gewerbepark 3 D-87477 Sulzberg

Phone: +49(0)8376-987 91-0 Fax: +49(0)8376-987 91-99 info@gertec-gmbh.de

Art.No.: 37388 Edition: 2022-02-09 Technical specifications are subject to change page 2 / 2