


Product Information Grout Plant IS-100-E

Grout Plants





Application areas:

- Anchor injection
- Grouting
- Cavity filling
- Micro tunnelling
- Ground injection
- Bentonite lubrication

Mixing of:

- Cement slurries
- Anchor grout
- Bentonite slurries
- Filling material for peripheral sealing
- Insulation slurries
- Fly ash slurries

Technical Data / Performance Data *

Mixing capacity (20 batches/h)	3,0	m3/h
Effective mixer volume	150	1
Mixing water minimum	50	1
Mixer filling level (bag loading)	940	mm
Buffer tank volume	300	1
Flow rate	0 - 200	l/min, continuously adjustable
Discharge pressure	max.100	bar, continuously limited
Solids grain size	max. 2	mm
Pressure connection	1 1⁄4"	IG
Water connection	Storz C	2" standard coupling DIN14307, max.6 bar; or Geka-claw coupling
Cleaning connection	DN 25	Geka-claw coupling
Power connection	CEE-plug	63 A, 5-pole
Power input	25	KW
Voltage	400	V; 50 Hz
Dimensions	1,75 x 2,15 x 2,4	m (L x W x H)
Weight	approx. 1700	kg

)* The specified performance data are non-binding values that differ significantly depending on dosing, mixing and discharge times.

GERTEC Maschinen- und Anlagenbau

> Gewerbepark 3 D-87477 Sulzberg

GmbH

Phone.: +49(0)8376-98791-0 Fax: +49(0)8376-98791-99 info@gertec-gmbh.de

Art.No.: 44141 Edition: 2022-02-20 Technical specifications are subject to change page 1/2



Product Information Grout Plant IS-100-E

Features:

- Batch mixer 150 I capacity (colloidal mixer; colloidal mixer; container stainless steel); fast running colloidal mixer; debagging grid with safety-end switch; adjustable filling bar for rough water level indication and water dosage; 3-way valve in the mixer-forced circulation; mixing tank draining
- Agitator tank 300 I capacity (container and agitator stainless steel); slow running agitator; with inclined tank bottom for better tank draining, tank wall with cleaning opening; tank lid with inspection port and safety-end switch
- ✓ **Double plunger pump** vertically arranged; automatic ball valves (inlet and exhaust valves)
- ✓ Water tank 150 I capacity, optical level indicator;
- ✓ Water dosage by manually operated ball valve
- ✓ Separate connection for cleaning hose including stopcock
- Rinsing operation; optional pumps for slurry or water possible; switching by manually operated valves
- Pump suction pipe with suction filter
- Pump pressure pipes with 2 lubricated high-pressure ball valves (1 x pressure relief for agitator tank, 1 x pressure port plunger pump) pressure pipe with pressure transmitter and visual pressure indicator (manometer 100 mm)
- ✓ Hydraulic aggregate with:
 - variable pump and fixed displacement pump
 - visual oil level indicator
 - return filter including visual contamination indicator;
 - oil minimum guard
 - venting nozzles
 - hydraulic control block with 2 hand wheels (1 x continuous adjustment of pump flow rate, 1 x continuous limiting of pump discharge pressure)
 - oil cooler
- Steel frame with working platform; central lifting eye; suitable seats for forklift and pallet truck handling; lifting eyes for transportation lock
- Electrical function and power control with the following display and control elements including protective cover (against vandalism)
 - Main switch ON/OFF
 - Mixer ON/OFF
 - Pump ON/OFF
 - Agitator ON/OFF
 - Diverse service counters
 - Operation hours counter pump
 - Plug socket 230 V

Accessories (not included in delivery):

- Remote control plunger pump(cable or radio)
- Electrical adjustment of flow rate (plunger pump)
- Electrical limitation discharge pressure (plunger pump)
- Digital display discharge pressure
- Workplace parasol (sun and weather protection)
- Data logging
- o Grouting hoses
- Cleaning hose
- o Water meter
- o Mixer scale
- LED launder (with tripod)
- o High-pressure cleaner

- Emergency-off-button
- Phase-control
- Combined fault display
- Operation mode switch
- Stroke counter pump
- Operation hours counter mixer

GERTEC Maschinen- und Anlagenbau GmbH

> Gewerbepark 3 D-87477 Sulzberg

Phone.: +49(0)8376-98791-0

Fax: +49(0)8376-98791-99 info@gertec-gmbh.de

Art.No.: 44141 Edition: 2022-02-20 Technical specifications are subject to change page 2/2